


Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



RIGID FOAM

A-Side

SDS

SAFETY DATA SHEET

Rigid Foam ISO

A-SIDE

Revised June 17, 2015

1. IDENTIFICATION

Product Identifier used on label:
Rigid Foam A-COMPONENT

Details of supplier of the Safety Data Sheet

Company:

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201

Emergency telephone number

CHEMTREC: 800-424-9300

2. HAZARDS IDENTIFICATION

Classification of the product

Acute Tox.	4 (Inhalation – mist)	Acute Toxicity
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Skin Corr./Irrit.	2	Skin corrosion/irritation
Skin Sens.	1B	Skin sensitization
Carc.	2	Carcinogenicity
STOT SE	3	Specific target organ toxicity – single exposure
STOT RE	2	Specific target organ toxicity – repeated exposure


Label Elements

Pictogram:



Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



SSS
SUPERSKINSYSTEMS

RIGID FOAM

A-Side

SDS

Signal Words

Danger

Hazard Statements

H318	Causes serious eye damage
H315	Causes skin irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H317	May cause an allergic skin reaction
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

Precautionary Statements (Prevention)

P280	Wear protective gloves and clothing with eye and face protection
P271	Use only outdoors or in a well-ventilated area
P260	Do not breathe dust/gas/mist/vapors
P201	Obtain special instructions before use
P261	Avoid breathing mist
P202	Do not handle until all safety precautions have been read and understood
P284	(In case of inadequate ventilation) wear respiratory protection
P272	Contaminated work clothing should not be allowed out of the workplace
P264	Wash with plenty of water and soap thoroughly after handling


Precautionary Statements (Response)

P312	Call a POISON CENTER or doctor/physician if you feel unwell
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing
P308 + P311	If exposed or concerned: Call a POISON CENTER or doctor/physician
P314	Get medical advice/attention if you feel unwell
P303 + P352	IF ON SKIN (or hair): Wash with plenty of soap and water
P333 + P311	If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician
P362 + P364	Take off contaminated clothing and wash before reuse
P332 + P313	If skin irritation occurs: Get medical advice/attention
P337 + P311	If eye irritation persists: Call a POISON CENTER or doctor/physician

Precautionary Statements (Storage)

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



RIGID FOAM

A-Side

SDS

P403 +P233 Store in a well-ventilated place. Keep container tightly closed
P405 Store locked up

Precautionary Statements (Disposal)

P501 Dispose of contents/container to hazardous or special waste collection point

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered

Emergency Overview

WARNING:

CONTAINS ISOCYANATES. INHALATION OF ISOCYANATE MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONG-TERM EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION. AVOID CONTACT WITH SKIN AND EYES. SKIN OR EYE CONTACT MAY CAUSE IRRITATION.

3. COMPOSITION /INFORMATION ON INGREDIENTS

<u>Component</u>	<u>%</u>	<u>CAS#</u>
Diphenylmethane Diisocyanate	30-70	26447-40-5
Polymethylene Polyphenylene Isocyanate	30-70	9016-87-9

4. FIRST AID

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:


Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

If on skin:

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



SSS
SUPERSKINSYSTEMS

RIGID FOAM

A-Side

SDS

If in eyes: In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Immediate medical attention required.

If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11., Eye irritation, skin irritation, allergic symptoms Information on: Gamma-butyrolactone Symptoms: Overexposure may cause:; weakness, chest discomfort, anxiety, nausea, diarrhea, headache

Hazards: Symptoms can appear later. Information on: Diphenylmethane-4,4'-diisocyanate (MDI) Hazards: Respiratory sensitization may result in allergic (asthma-like) signs in the lower respiratory tract including wheezing, shortness of breath and difficulty breathing, the onset of which may be delayed. Repeated inhalation of high concentrations may cause lung damage, including reduced lung function, which may be permanent. Substances eliciting lower respiratory tract irritation may worsen the asthma-like reactions that may be produced by product exposures.

Indication of any immediate medical attention and special treatment needed

Note to physician

Antidote:	Specific antidotes or neutralizers to isocyanates do not exist
Treatment:	Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient

5. FIRE FIGHTING MEASURES

Extinguishing Media

Suitable extinguishing media: water spray, dry powder, carbon dioxide, foam

Special hazards arising from the substance or mixture

Hazards during fire-fighting: nitrous gases, fumes/smoke, isocyanate, vapor

Advice for fire-fighters


Protective equipment for fire-fighting: Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information

Keep containers cool by spraying with water if exposed to fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



SSS
SUPERSKINSYSTEMS

RIGID FOAM

A-Side

SDS

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Absorb isocyanate with suitable absorbent material (see § 40 CFR, sections 260, 264 and 265 for further information). Shovel into open container. Do not make container pressure tight. Move container to a well-ventilated area (outside). Spill area can be decontaminated with the following recommended decontamination solution: Mixture of 90 % water, 8 % concentrated ammonia, 2 % detergent. Add at a 10 to 1 ratio. Allow to stand for at least 48 hours to allow escape of evolved carbon dioxide.

For large amounts: If temporary control of isocyanate vapor is required, a blanket of protein foam or other suitable foam (available from most fire departments) may be placed over the spill. Transfer as much liquid as possible via pump or vacuum device into closed but not sealed containers for disposal.

For residues: The following measures should be taken for final cleanup: Wash down spill area with decontamination solution. Allow solution to stand for at least 10 minutes. Dike spillage.

7. HANDLING AND STORAGE

Precautions for safe handling

Provide suitable exhaust ventilation at the processing machines. Ensure thorough ventilation of stores and work areas. Avoid aerosol formation. When handling heated product, vapors of the product should be ventilated, and respiratory protection used. Wear respiratory protection when spraying. Danger of bursting when sealed gastight. Protect against moisture. If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.

Protection against fire and explosion:

No explosion proofing necessary.


Conditions for safe storage, including any incompatibilities

Keep away from water. Segregate from foods and animal feeds. Segregate from acids and bases. Segregate from bases.

Suitable materials for containers: Carbon steel (Iron), High density polyethylene (HDPE), Low density polyethylene (LDPE), Stainless steel 1.4301 (V2)

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



SSS
SUPERSKINSYSTEMS

RIGID FOAM

A-Side

SDS

Further information on storage conditions: Formation of CO₂ and build up of pressure possible. Keep container tightly closed and in a well-ventilated place. Outage of containers should be filled with dry inert gas at atmospheric pressure to avoid reaction with moisture.

Storage stability: Storage temperature: 16 - 27 °C

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Components with occupational exposure limits

Diphenylmethane-4,4'-diisocyanate (MDI)

OSHA PEL CLV 0.02 ppm 0.2 mg/m³ ; CLV 0.02 ppm 0.2 mg/m³

ACGIH TLV TWA value 0.005 ppm

Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection:

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place. For emergency or non-routine, high exposure situations, including confined space entry, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

Hand protection:

Chemical resistant protective gloves should be worn to prevent all skin contact. Suitable materials may include, chloroprene rubber (Neoprene), nitrile rubber (Buna N), chlorinated polyethylene, polyvinylchloride (Pylox), butyl rubber, depending upon conditions of use.

Eye protection:

Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.


Body protection:

Cover as much of the exposed skin as possible to prevent all skin contact. Suitable materials may include, saran-coated material, depending upon conditions of use.

General safety and hygiene measures:

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



SSS
SUPERSKINSYSTEMS

RIGID FOAM

A-Side

SDS

Wear protective clothing as necessary to prevent contact. Eye wash fountains and safety showers must be easily accessible. Observe the appropriate PEL or TLV value. Wash soiled clothing immediately. Contaminated equipment or clothing should be cleaned after each use or disposed of.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid
Odor:	Earthy, Musty Odor
Odor Threshold:	N/A
Color:	Dark Brown
pH Value:	N/A
Freezing Point:	-13 degrees C
Boiling Point:	>204 degrees C (decomposes)
Flash Point:	>230 degrees C
Flammability:	Not flammable
Autoignition:	>470 degrees C
Vapor Pressure:	0.00001 mmHg
Density:	9.4 lbs./gal.
Relative Density:	1.25 @ 25 degrees C
Vapor Density:	N/A
Self-Ignition Temperature:	This product is not classified as self-igniting
Thermal Deomposition:	No decomposition if handled and stored as prescribed/indicated.
Viscosity, dynamic:	200 +/- 50 mPa.s
Solubility in water:	Reacts with water
Miscibility with water:	Reacts with water

10. STABILITY AND REACTIVITY

Reactivity

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

Not an oxidizer.


Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



RIGID FOAM

A-Side

SDS

Reacts with water, with formation of carbon dioxide. Risk of bursting. Reacts with alcohols. Reacts with acids. Reacts with alkalis. Reacts with amines. Risk of exothermic reaction. Risk of polymerization. Contact with certain rubbers and plastics can cause brittleness of the substance/product with subsequent loss in strength.

Conditions to avoid

Avoid moisture.

Incompatible materials

Acids, amines, alcohols, water, Alkaline, strong bases, Substances/products that react with isocyanates.

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide, nitrogen oxides, aromatic isocyanates, gases/vapors

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. TOXICOLOGICAL INFORMATION

Oral

Information on: Diphenylmethane-4,4'-diisocyanate (MDI)

Type of value: LD50

Species: rat (male/female)

Value: > 2,200 mg/kg (Directive 84/449/EEC, B.1)

Inhalation

Type of value: LC50 Inhalation (4 hrs.)

Species: rat (male/female)

Value: 370 Aerosol

Dermal

Information on: Diphenylmethane-4,4'-diisocyanate (MDI)

Type of value: LD50

Species: rabbit (male/female)


Value: > 10,000 mg/kg

Other Toxicity Data:

Irritation

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



SSS
SUPERSKINSYSTEMS

RIGID FOAM

A-Side

SDS

Inhalation: Polymeric MDI has an extremely low vapor pressure and is difficult to achieve vapor concentrations necessary for inhalation toxicity testing. The desired vapor concentrations can only be obtained by heating the Polymeric MDI source. The vapor evolved readily and condenses to an aerosol in the inhalation exposure chambers. Therefore, it is likely that an aerosol rather than a vapor is present. Symptoms of severe irritation and deaths occurred at 13.6 mg/m³. Less severe irritation and no deaths occurred at 4.9 mg/m³. There were no visible effects at 2.2 mg/m³.

Eyes: Commercial Polymeric MDI caused eye irritation in rabbits, which cleared after 24 hours.

Skin: Application of single doses of 2.5, 3.9, 6.0 and 9.4 mg/kg Polymeric MDI to abraded skin of rabbits, under a cover for 24 hours, caused only minor, local reversible skin changes.

Corrosivity

Not available

Sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Isocyanates are known to cause skin and respiratory sensitization in humans. Animal tests have indicated that respiratory sensitization can result from skin contact with diisocyanate.

Carcinogenicity

This preparation does not contain any component that is considered a human carcinogen by IARC (international Agency for Research on Cancer), ACGIH (American Conference of Governmental Industrial Hygienists), OSHA, or NTP (National Toxicology Program).

12. ECOLOGICAL INFORMATION

Toxicity to fish

LC50 (96 h) > 1,000 mg/l, Zebra Fish

Aquatic invertebrates

EC50 (24 h) > 1,000 mg/l, Daphnia magna

Aquatic plants

EC50 (72 h) 1,640 mg/l (growth rate), Scenedesmus subspicatus

Persistence and degradability


Assessment biodegradation and elimination (H₂O)

Poorly biodegradable. The product is unstable in water. The elimination data also refer to products of hydrolysis.

Assessment of stability in water

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



SSS
SUPERSKINSYSTEMS

RIGID FOAM

A-Side

SDS

In contact with water the substance will hydrolyse slowly.

Information on Stability in Water (Hydrolysis)

t_{1/2} 20 h (25 °C)

Bioaccumulative potential

Not Available

Mobility in soil

Not Available

13. DISPOSAL CONSIDERATION (INCLUDING CONTAINER)

Waste disposal of substance:

Incinerate or dispose of in a licensed facility. Do not discharge substance/product into sewer system.

Container disposal:

DRUMS:

Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Do not attempt to refill or clean containers since residue is difficult to remove. Under no circumstances should empty drums be burned or cut open with gas or electric torch as toxic decomposition products may be liberated. Do not reuse empty containers.

14. TRANSPORT AND INFORMATION

Land Transport

US DOT

Not classified as a dangerous good under transport regulations

Sea Transport

IMDG

Not classified as a dangerous good under transport regulations

Air Transport

IATA/ICAO


Not classified as a dangerous good under transport regulations

Further Regulations

DOT: This product is regulated if the amount in a single receptacle exceeds the Reportable Quantity (RQ). Please refer to Section 15 of this SDS for the RQ for this product.

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



SSS
SUPERSKINSYSTEMS

RIGID FOAM

A-Side

SDS

15. REGULATORY INFORMATION:

USA

TSCA Status: All component substances of this mixture are listed on the TSCA Inventory.

SARA Title III: Sec. 313 MDI 1% de minimis, CERCLA RQ MDI 5,000 lbs.

California Prop. 65: The component substances are not listed

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

WHMIS Classification: D1A Immediate and serious toxic effects, D2A Material causing other toxic effects

NSNR Status: All substances in this preparation are listed on the DSL.

NPRI Substances: Polymethylene Polyphenylene Isocyanate and MDI are NPRI reportable substances (Part 1, Group 1)

EU

European Inventories: All substances in this preparation are listed in EINECS. All component substances are pre-registered substances under REACH.

Other International Inventories

Australia: All component substances are present on the Inventory of Chemical Substances (AICS)

China: All component substances are present on the Chemical Inventory

Japan: All component substances are present on the Inventory – Existing and Evaluated Chemical Substances. Polymeric MDI 7-872; MDI KE-23829.

Korea: All component substances are present on the Inventory – Existing and Evaluated Chemical Substances. Polymeric MDI KI-21487; MDI KE-23829.

New Zealand: All component substances are present on the Chemical Inventory

Philippines: All component substances are present on the Inventory of Chemicals and Chemical Substances (PICCS).

NFPA Hazard Codes:


Health: 2 Fire: 1 Reactivity: 1 Special: N/A

HMIS III Rating:

Health: 2 Flammability: 1 Physical Hazard: 1

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



SSS
SUPERSKINSYSTEMS

RIGID FOAM

A-Side

SDS

16. OTHER INFORMATION

SDS Prepared by:

Superskinsystems, Inc.

SDS Prepared on: 06/17/2015


Disclaimer/Statement of Liability:

The data in this Safety Data Sheet is offered for your consideration, investigation and verification. The data is presented in good faith and was obtained from sources SuperSkinSystems Inc. believes to be reliable. SuperSkinSystems Inc. however, makes no representation as to the completeness or accuracy. SuperSkinSystems Inc. makes no warranty, express or implied, with respect to the data contained herein. SuperSkinSystems Inc. cannot anticipate all conditions under which this data and the product may be used. The conditions of handling, storage, use, and disposal of the product are beyond SuperSkinSystems Inc. control. Thus, we expressly disclaim responsibility or liability for any loss, damage or expense arising out of reliance on the information contained herein. You are advised to make your own determination as to safety, suitability and appropriate manner of handling, storage, use and disposal.

END OF SAFETY DATA SHEET

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



SSS
SUPERSKINSYSTEMS

Rigid Pour Foam

B-Side

SDS

SAFETY DATA SHEET

Rigid Pour Foam Resin

B-SIDE

Revised June 17, 2015

1. IDENTIFICATION

Product Identifier used on label:
Rigid Pour Foam B-SIDE

Details of supplier of the Safety Data Sheet

Company:

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201

Emergency telephone number

CHEMTREC: 800-424-9300

2. HAZARDS IDENTIFICATION

Classification of the product

Not Classified

Label Elements

Pictogram:



Signal Words

Warning


Hazard Statements

H302

Harmful if swallowed

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



Rigid Pour Foam

B-Side

SDS

H319 Causes serious eye irritation

Precautionary Statements (Prevention)

P264 Wash exposed skin thoroughly after handling
P270 Do not eat, drink or smoke when using this product
P280 Wear protective gloves/clothing and eye/face protection.

Precautionary Statements (Response)

P330 Call a POISON CENTER or doctor/physician if you feel unwell
P301 + P312 IF SWALLOWED: Call POISON CENTER or doctor/physician if you feel unwell
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337 + P313 Get medical advice/attention

Precautionary Statements (Disposal)

P501 Dispose of contents/container to hazardous or special waste collection point

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered

3. COMPOSITION /INFORMATION ON INGREDIENTS

<u>Component</u>	<u>%</u>	<u>CAS#</u>
Catalyst	1-5	Proprietary
Surfactant	1-2	Proprietary
Polyether Polyol	40-60	Proprietary
Soy Polyol	15-30	Proprietary

4. FIRST AID

Move exposed person to fresh air. If breathing is labored, oxygen should be administered by qualified personnel.


In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

After contact with skin, wash immediately with plenty of warm, soapy water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Provided the patient is conscious, wash out mouth with water. Get medical attention if symptoms appear.

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



SSS
SUPERSKINSYSTEMS

Rigid Pour Foam

B-Side

SDS

5. FIRE FIGHTING MEASURES

Extinguishing Media: Water, Foam, CO2 or dry powder.

Caution:

Heating or fire can release toxic gas.

Hazardous decomposition products:

Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, and hydrocarbons.

Special protective actions for fire-fighters:

Promptly isolate the scene by removing all persons from the vicinity of the incident, if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet and protective clothing should be worn.

6. ACCIDENTAL RELEASE MEASURES

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).


Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. HANDLING AND STORAGE

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get into eyes.

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



SSS
SUPERSKINSYSTEMS

Rigid Pour Foam

B-Side

SDS

Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and may be hazardous.

Material is to be stored in accordance with local regulations. Store in original container protected from direct sunlight in a dry and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers.

Use appropriate containment to avoid environmental contamination.

Unsuitable containers: Do not store in containers made of copper, copper alloys or galvanized surfaces.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Engineering Controls: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Smell is not an adequate indicator of hazard.

Ventilation: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Protective Gear: In case of inadequate ventilation, wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all time when handling chemical products if a risk assessment indicates this is necessary.

Safety eyewear complying with an approved standard should be used when a risk assessment indicate this is necessary to avoid exposure to liquid splashes, mists or dusts.


Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid
Odor: Mild

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



SSS

S U P E R S K I N S Y S T E M S

Rigid Pour Foam

B-Side

SDS

Odor Threshold:	N/A
Color:	As color specified
pH Value:	N/A
Boiling Point:	>212 degrees C
Flash Point:	>94 degrees C
Flammability:	Not flammable
Vapor Density:	N/A
Viscosity:	N/A
Self-Ignition Temperature:	This product is not classified as self-igniting
Thermal Decomposition:	No decomposition if handled and stored as prescribed/indicated.
Solubility in water:	Miscible
Evaporation rate:	N/A
% Weight Volatile (VOC):	0.00

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at room temperature. No specific test data related to reactivity is available for this product or its ingredients.

Hazardous reactions: None known. Stable under normal conditions.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity Data:

Oral rat, Acute LD50, >2000 mg/kg

Dermal rabbit, Acute LD50, >2000 mg/kg

Inhalation rat, Acute LC50 4 hrs., >5 mg/l (Dust/Mist)

Local Effects on Skin and Eye:

Acute Irritation dermal – Not Irritating

Acute Irritation eye – Not Irritating

Allergic Sensitization:

No Data

Genotoxicity:


No Data

Specific Target Organ:

No Data

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



Rigid Pour Foam

B-Side

SDS

Effects of Overexposure

N/A

Carcinogenicity

None

12. ECOLOGICAL INFORMATION

Only component information is listed, if any. No testing has been performed on this mixture as it relates to ecological impact.

13. DISPOSAL CONSIDERATION (INCLUDING CONTAINER)

The generation of waste should be avoided or minimized by using excess product in an alternate, beneficial application wherever possible.

Empty containers may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material, runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT AND INFORMATION

Land Transport

US DOT

Not Regulated

Sea Transport

IMDG

Not Regulated

Air Transport


IATA/ICAO

Not Regulated

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



SSS
SUPERSKINSYSTEMS

Rigid Pour Foam

B-Side

SDS

variations in regulations. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION:

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30, unless listed below:

-None

This product contains the following substance(s), which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and which are listed in 40 CFR 372:

-None

NFPA Hazard Codes:

Health: 1 Fire: 1 Reactivity: 0 Special: N/A

HMIS III Rating:

Health: 1 Flammability: 1 Physical Hazard: 0

16. OTHER INFORMATION

SDS Prepared by:

Superskinsystems, Inc.


SDS Prepared on: 06/17/2015

Disclaimer/Statement of Liability:

The data in this Safety Data Sheet is offered for your consideration, investigation and verification. The data is presented in good faith and was obtained from sources SuperSkinSystems Inc. believes to be reliable. SuperSkinSystems Inc. however, makes no representation as to the completeness or accuracy. SuperSkinSystems Inc. makes no warranty, express or implied, with respect to the data contained herein. SuperSkinSystems Inc. cannot anticipate all conditions under which this data and the product may be used. The conditions of handling, storage, use, and disposal of the product are beyond SuperSkinSystems Inc. control. Thus, we expressly disclaim responsibility or liability for any loss, damage or expense arising out of reliance on the information contained herein. You are advised to make your own determination as to safety, suitability and appropriate manner of handling, storage, use and disposal.

Superskinsystems, Inc.
322 Industrial Park Dr.
Lawrenceville, GA 30046
Phone: 404-435-4201
404-229-8343

CHEMTREC: 800-424-9300



Rigid Pour Foam

B-Side

SDS

END OF SAFETY DATA SHEET